

Input

Input voltage range	85 - 265VAC, 40-70Hz (other frequency on request)
Inrush current	max. 40A, limited by NTC
No-load input current	< 90mA at U _{in} 115VAC
Switch-on time	typ. 1,5s
Hold-up time	> 10ms at U _{in} 115VAC
Fuse	5AT provided external
Turn on	U _{in} ≥ 70VAC
Spikes	acc. EN 61000-4-5, Class 3
Bursts	acc. EN 61000-4-4, Level 3

Output

Output voltage	220VDC standard setting, (adjustable from 200VDC to 250VDC only by factory).
Output current	0,8ADC up to U _{out} 250VDC
Line regulation/ Load regulation	< ±2%, measured directly at the connection terminal
Ripple	<2200mV p-p typ
Response time	typ. 2ms
Load transient 10-100-10%	typ. 6%
On/off overshoot	none
Overload protection	electronically
Over voltage protection	> 275VDC switch off, not automatic return, no effect on external over voltage
Decoupling Diode	in the output
Alarm Signals	over potential free contacts, when U _{out} is <175VDC (NOC=open, NCC=closed).

General

Operating temperature	-20°C to +75°C temperature > +55°C automatically derating of output current to 50%
Storage temperature	-40°C to +85°C
Humidity	max. 75% without condensation,
Efficiency at full load	>80%,
Power dissipation	app. 32W

Construction

Isolation	acc. EN 50178, EN 60950, Class I
RFI-interference	acc. EN 50178, EN 60950
EMC / CE	acc. EN 55011 Class "A" EN 61000-6-4, EN 61000-6-2 Grounding of input and/or output potentials and/or connecting input to output may cause changes of EMC and/or ripple values.
Protection class	I acc. EN 61140
Visual Indications	green LED U _{out} = Output voltage ok (DC ok.)
Case	for rail mount, 35mm rail EN50022, Alu varnished, RAL7035
Connection	plug-in terminals on front panel
Weight	app. 1,5kg