

DC/DC-Converter Series P300 – 19“ Cassette 150 Watt

- 19“ Cassette
- Input, output, case isolated against each other
- SELV
- Inrush current limit and diode for polarity protection
- Output decoupling diode with DC-OK-alarm

Input Voltage		Output Voltage		Output Current	Type
VDC	min. - max.	VDC	Adjustable by factory min. -max.	max.* ADC	
48	38 - 62	24	21 - 28	6,0	P334
48	38 - 62	48	42 - 56	3,0	P339
48	38 - 62	60	53 - 70	2,5	P336
60	50 - 80	24	21 - 28	6,0	P344
60	50 - 80	48	42 - 56	3,0	P349
60	50 - 80	60	53 - 70	2,5	P346
110	80 - 160	24	21 - 28	6,0	P354
110	80 - 160	48	42 - 56	3,0	P359
110	80 - 160	60	53 - 70	2,5	P356
220	160 - 280	24	21 - 28	6,0	P374
220	160 - 280	48	42 - 56	3,0	P379
220	160 - 280	60	53 - 70	2,5	P376

* see also Technical Data



Construction 19"-cassette 3U, 14TE, depth 166mm

Connectors mating connector H15

Weight app. 1,0kg

Output	Overload	Current limit UI- characteristic
	OVP	Adjusted to 1,25 x Unom
	Sense	Internally
	Function controll	LED on front panel
	Output decoupling diode with DC-OK-alarm	Alarm at $U_{out} < 0,8 U_{out}$, pot.free relay contacts NOC/NCC
Input	Turn off at U_{in}	Fixed $<95\% U_{min} >105\% U_{max}$
Additional Informations	Details „Technical Data „	