

DC/DC-Converter Series P500 – 19“ Cassette 350 Watt

- 19“ Cassette
- Input, output, case isolated against each other
- SELV
- Inrush current limit and diode for polarity protection
- Output decoupling diode with DC-OK-alarm
- Boost-function, output current app. 4 x Inom for 10ms ≤ t ≤ 15ms
- Over temperature protection

Input Voltage		Output Voltage		Output Current	Type
VDC	min. - max.	VDC	Adjustable by factory min. -max.	max*. ADC	
110	80 – 160	24	21 - 28	14,0	P554
110	80 – 160	48	42 - 56	7,0	P559
110	80 – 160	60	53 - 70	5,5	P556
220	160 – 280	24	21 - 28	14,0	P574
220	160 – 280	48	42 - 56	7,0	P579
220	160 – 280	60	53 - 70	5,5	P576

*also see Technical Data



Construction 19“-cassette 3U, 28TE, depth 166mm

Connectors mating connector H15

Weight app. 2,0kg

Output	Overload	Current limit UI- characteristic
	OVP	Adjusted to 1,25 x Unom
	Sense	Internally
	Function controll	LED on front panel
	Output decoupling diode with DC-OK-alarm	Alarm at $U_{out} < 0,8 U_{out}$, pot.free relay contacts NOC/NCC
Input	Turn off at U_{in}	Fixed $<95\% U_{min} >105\% U_{max}$
Additional Informations	Details „Technical Data „	