

## Input

Input voltage range	50-80VDC
Inrush current	max. 32ADC limited by NTC 2,5Ω
No-load input current	app.65mA at 60VDC
Switch-on time	typ. 2s
Hold-up time	typ. 3,5ms at 60VDC and nominal load
Polarity protection	cross diode in the input <b>with fusing (external): MCB 10A, B-characteristic or fuse 8A</b>
Turn on/off	≤ 45 VDC / ≥ 82VDC
Spikes	acc. EN 61000-4-5, Class 3
Bursts	acc. EN 61000-4-4, Level 3

## Output

Output voltage	48VDC standard setting, (adjustable from 42VDC to 56VDC only by factory).
Output current	3ADC up to Uout 50VDC, > 50VDC 2,7ADC
Line regulation, Load regulation	< ±2%, measured directly at the connection terminal
Ripple	<500mV p-p typ
Response time	typ. 2ms
Load transient 10-100-10%	typ. 6%
On/off overshoot	none
Overload protection	electronically
Over voltage protection	> 60VDC switch off, not automatic return, no effect on external over voltage
Decoupling Diode	in the output
Alarm Signals	over potential free contacts, when Uout is <40VDC (NOC=open, NCC=closed).

## General

Operating temperature	-25°C to +55°C Derating 2,5% /°C for temperature +55°C up to max. 75°C necessary.
Storage temperature	-40°C to +85°C
Humidity	max. 75% without condensation,
Efficiency at full load	>85%,
Power dissipation	app. 30W

## Construction / Isolation

RFI-interference	acc. EN 55011 Class "A"
EMC / CE	EN 61000-6-4, EN 61000-6-2 Grounding of input and/or output potentials and/or connecting input to output may cause changes of EMC and/or ripple values
Protection class	I acc. EN 61140
Visual Indications	green LED Uout = Output voltage ok (DC ok.)
Case	for chassis mount, Alu varnished, RAL7035
Connection	plug-in terminals on front panel
Weight	app. 1kg