

Input

| | |
|-----------------------|------------------------------|
| Input voltage range | 80-160VDC |
| Inrush current | max. 23ADC limited by NTC 7Ω |
| Fuse | 6,3 AT externally |
| No-load input current | app. 50mA at 110VDC |
| Switch-on time | typ. 2s |
| Hold-up time | typ. 15ms at 110VDC |
| Polarity protection | yes |
| Turn on/off | ≤ 76 VDC / ≥ 168VDC |
| Spikes | acc. EN 61000-4-5, Class 3 |
| Bursts | acc. EN 61000-4-4, Level 3 |

Output

| | |
|---------------------------|--|
| Output voltage | 60VDC standard setting, (adjustable from 53VDC to 70VDC only by factory). |
| Output current | 5,5ADC up to Uout 61VDC, >61VDC 5ADC |
| Boost Function | max. output current app. 22ADC for 10ms ≤ t ≤ 15ms |
| Line regulation | |
| Load regulation | < ±2%, measured directly at the connection terminal |
| Ripple | <600mV p-p typ |
| Response time | typ. 2ms |
| Load transient 10-100-10% | typ. 6% |
| On/off overshoot | none |
| Overload protection | electronically |
| Over voltage protection | > 75VDC switch off, not automatic return, no effect on external over voltage |
| Sense lines | Externally, on connector (function without connected Sense possible) |
| Decoupling Diode | in the output |
| Alarm Signals | over potential free contacts, when Uout is <50VDC (NOC=open, NCC=closed). |

General

| | |
|-----------------------------|--|
| Operating temperature | -25°C to +55°C Derating 2,5% /°C for temperature +55°C up to max. 75°C necessary. |
| Over temperature protection | unit switch off if internally temperature is too high, automatically switch on after cooling |
| Storage temperature | -40°C to +85°C |
| Humidity | 75% without condensation, |
| Efficiency at full load | >90%, |
| Power dissipation | app. 68W |
| Over temperature protection | shut off, at hot spot off about 100°C. Automatically restart after cooling down. |

Construction / Isolation

| | |
|--------------------|---|
| RFI-interference | acc. EN 61010, SELV |
| EMC / CE | acc. EN 55011 Class "A" EN 61000-6-4, EN 61000-6-2 Grounding of input and/or output potentials and/or connecting input to output may cause changes of EMC and/or ripple values. |
| Protection class | I acc. EN 61140 |
| Visual Indications | green LED Uout = Output voltage ok (DC ok.) |
| Case | 19" cassette, 3U, 28TE, depth app. 166mm, elox alu front panel, RAL7035 |
| Connection | Connector H15 |
| Weight | app. 1kg |