

Input

| | |
|-----------------------|--|
| Input voltage range | 38 - 62VDC |
| Inrush current | max. 25ADC limited by NTC 2,5Ω |
| No-load input current | app. 100mA at 48VDC |
| Switch-on time | typ. 2s |
| Hold-up time | typ. 3ms at 48VDC and nominal load |
| Polarity protection | cross diode in the input with fusing (external): MCB 10A, B-characteristic or fuse 8A |
| Turn on/off | ≤ 35 VDC / ≥ 65VDC |
| Spikes | acc. EN 61000-4-5, Class 3 |
| Bursts | acc. EN 61000-4-4, Level 3 |

Output

| | |
|-------------------------------------|---|
| Output voltage | 24VDC standard setting, (adjustable from 21VDC to 28VDC only by factory). |
| Output current | 8ADC up to Uout 25VDC, > 25VDC 7,2ADC |
| Line regulation/ Load regulation | < 2%, measured directly at the connection terminal |
| Ripple | <250mV p-p typ |
| Response time | typ. 2ms |
| Load transient 10-100-10% | typ. 6% |
| On/off overshoot | none |
| Overload protection | electronically |
| Over voltage protection | > 30 VDC switch off, not automatic return, no effect on external over voltage |
| Sense lines | Externally, on connector (function without connected Sense possible) |
| Decoupling Diode | in the output |
| Alarm Signals | over potential free contacts, when Uout is <20VDC (NOC=open, NCC=closed). |

General

| | |
|-------------------------|--|
| Operating temperature | -25°C to +55°C Derating 2,5% /°C for temperature +55°C up to max. 75°C necessary. |
| Storage temperature | -40°C to +85°C |
| Humidity | max. 75% without condensation, |
| Efficiency at full load | >85%, |
| Power dissipation | app. 35W |

Construction / Isolation

| | |
|--------------------|--|
| RFI-interference | acc. EN 55011 Class "A" |
| EMC / CE | EN 61000-6-4, EN 61000-6-2 Grounding of input and/or output potentials and/or connecting input to output may cause changes of EMC and/or ripple values. |
| Protection class | I acc. EN 61140 |
| Visual Indications | green LED Uout = Output voltage ok (DC ok.) |
| Case | 19" cassette, 3U, 14TE, depth app. 166mm, elox alu front panel, RAL7035 |
| Connection | Connector H15 |
| Weight | app. 1kg |