

## Input

Input voltage range	160-280VDC
Inrush current	max. 40ADC limited by NTC 7Ω
Fuse	6,3 AT externally
No-load input current	app. 25mA at 220VDC
Switch-on time	typ. 2s
Hold-up time	typ. 15ms at 220VDC
Polarity protection	yes
Turn on/off	≤ 144VDC / ≥ 294VDC
Spikes	acc. EN 61000-4-5, Class 3
Bursts	acc. EN 61000-4-4, Level 3

## Output

Output voltage	24 VDC (adjustable 21VDC-28VDC only by factory)
Output current	14ADC up to Uout 25VDC, Uout >25VDC 12.5ADC
Boost Function	max. output current app. 56ADC for 10ms ≤ t ≤ 15ms
Line regulation/ Load regulation	< 2%, measured directly at the connection terminal
Ripple	<250mV p-p typ
Response time	typ. 2ms
Load transient 10-100-10%	typ. 6%
On/off overshoot	none
Overload protection	electronically
Over voltage protection	> 30 VDC switch off, not automatic return, no effect on external over voltage
Decoupling Diode	in the output
Alarm Signals	over potential free contacts, when Uout is <20VDC (NOC=open, NCC=closed).

## General

Operating temperature	-25°C to +55°C Derating 2,5% /°C for temperature +55°C up to max. 75°C necessary.
Over temperature protection	unit switch off if internally temperature is too high, automatically switch on after cooling
Storage temperature	-40°C to +85°C
Humidity	75% without condensation,
Efficiency at full load	>90%,
Power dissipation	app. 68W
Over temperature protection	shut off, at hot spot off about 100°C. Automatically restart after cooling down.

## Construction / Isolation

RFI-interference	acc. EN 55011 Class "A"
EMC / CE	EN 61000-6-4, EN 61000-6-2 Grounding of input and/or output potentials and/or connecting input to output may cause changes of EMC and/or ripple values.
Protection class	I acc. EN 61140
Visual Indications	green LED Uout = Output voltage ok (DC ok.)
Case	for rail mount, 35mm rail EN50022, Alu varnished, RAL7035
Connection	plug-in terminals on front panel
Weight	app. 2kg