

AC/DC Power Supplies with wide range input

Series PW3400CM – Chassis Mount max. 1000 Watt Processor controlled

- Chassis mount
- Input, output, case isolated against each other
- SELV up to U_{out} 60VDC
- Inrush current limit
- Inhibit primary and additional with 24VDC-Signal
- Active ORing decoupling
- Boost-function, output current app. 3 - 4 x I_{nom} for 10ms ≤ t ≤ 15ms
- Over temperature protection
- Current sharing for parallel operation
- Interface IO-Link (option)

Input Voltage Range	Output Voltage		Output Current Type max.* ADC	Type
	VDC	Adjustable by factory min. - max. VDC		
VAC 40-70Hz				
85 - 265	24	21 - 28	42	PW3494CM
85 - 265	48	42 - 56	21	PW3499CM
85 - 265	60	53 - 70	17	PW3496CM
85 - 265	110	110 - 130	9	PW3497CM
85 - 265	220	200 - 250	4,5	PW3498CM

*see also Technical Data

Construction	chassis mount
Connectors	plug-in terminals on front panel
Weight	app. 8kg

Output	Overload	Current limit UI- characteristic
	OVP	Adjusted
	Sense	Internally
	Function controll	LED's gr. U _{in} , U _{out} ; LED rd. Failure on front panel
	Output decoupling diode with DC-OK-alarm	Alarm via pot. free relay contacts NOC/NCC or Interface
Input	Turn on/ off at U _{in}	IO-link (optional)
Additional Informations	Fixed	
	Details „Technical Data „	