

AC/DC Power Supplies with wide range input

Series PW400CM – Chassis Mount max. 200 Watt

- Chassis mount
- Input, output, case isolated against each other
- SELV
- Inrush current limit with NTC
- Output decoupling diode with DC-OK-alarm
- Operating temperature -20 bis + 75°C, > 55°C automatical derating.

Input Voltage Range VDC 40-70Hz min. - max.	Output Voltage		Output Current max.* ADC	Type
	VDC	adjustable (only by factory) min. - max.		
85 - 265	24	21 - 26	8,0	PW494CM
85 - 265	48	42 - 52	4,0	PW499CM
85 - 265	60	53 - 66	3,2	PW496CM
85 - 265	110	100-125	1,6	PW497CM
85 - 265	220	200-250	0,8	PW498CM

*see also technical data



Construction	chassis mount
Connectors	plug-in terminals on front panel
Weight	app. 1,5kg

Output	Overload	Current limit UI- characteristic
	OVP	Adjusted to 1,25 x Unom
	Sense	Internally
	Function controll	LED on front panel
	Output decoupling diode with DC-OK-alarm	Alarm at $U_{out} < 0,8 U_{out}$, pot.free relay contacts NOC/NCC
Input	Turn off at U_{in}	Fixed $<95\% U_{min} >105\% U_{max}$
Additional Informations	Details „Technical Data „	