

AC/DC Power Supplies with wide range input

Series PW400 – 19“ Cassette max. 200 Watt

- 19“ Cassette
- Input, output, case isolated against each other
- SELV
- Inrush current limit with NTC
- Output decoupling diode with DC-OK-alarm
- Operating temperature -20 bis + 75°C, > 55°C automatical derating.

Input Voltage Range	Output Voltage		Output Current	Type
	VDC	adjustable (only by factory) min. - max.		
VDC 40-70Hz min. - max.	VDC	adjustable (only by factory) min. - max.	max.* ADC	
85 - 265	24	21 - 26	8,0	PW494
85 - 265	48	42 - 52	4,0	PW499
85 - 265	60	53 - 66	3,2	PW496
85 - 265	110	100-125	1,6	PW497
85 - 265	220	200-250	0,8	PW498

*see also technical data



Construction 19"-cassette 3U, 14TE, depth 166mm

Connectors mating connector H15

Weight app. 1,0kg

Output	Overload	Current limit UI- characteristic
	OVP	Adjusted to 1,25 x Unom
	Sense	Internally
	Function controll	LED on front panel
	Output decoupling diode with DC-OK-alarm	Alarm at $U_{out} < 0,8 U_{out}$, pot.free relay contacts NOC/NCC
Input	Turn off at U_{in}	Fixed $<95\% U_{min} >105\% U_{max}$
Additional Informations	Details „Technical Data „	