

Input

Input voltage range	17 - 75VDC
Inrush current	max. 30ADC limited by NTC
No-load input current	app. 380mA at U _{in} 24VDC
Switch-on time	typ. 1s
Hold-up time	> 5ms at 48VDC and nominal load
Polarity protection	existing
Fuse	10AT provided external
Turn on	U _{in} ≥ 15,5VDC
Spikes	acc. EN 61000-4-5, Class 3
Bursts	acc. EN 61000-4-4, Level 3

Output

Output voltage	110VDC standard setting, (adjustable from 100VDC to 130VDC only by factory).
Output current at U _{in} > 35VDC	1,6ADC up to U _{out} 130VDC
U _{in} < 35VDC	0,8ADC up to U _{out} 130VDC
Line regulation/ Load regulation	< ±2%, measured directly at the connection terminal
Ripple	<1100mV p-p typ
Response time	typ. 2ms
Load transient 10-100-10%	typ. 6%
On/off overshoot	none
Overload protection	electronically
Over voltage protection	> 145 VDC switch off, not automatic return, no effect on external over voltage
Decoupling Diode	in the output
Alarm Signals	over potential free contacts, when U _{out} is <88VDC (NOC=open, NCC=closed).

General

Operating temperature	-20°C to +75°C temperature > +55°C automatically derating of output current to 50%
Storage temperature	-40°C to +85°C
Humidity	max. 75% without condensation,
Efficiency at full load	>80%,
Power dissipation	app. 32W

Construction

Isolation	acc. EN 50178, EN 60950, Class I
RFI-interference	acc. EN 50178, EN 60950
EMC / CE	acc. EN 55011 Class "A" EN 61000-6-4, EN 61000-6-2 Grounding of input and/or output potentials and/or connecting input to output may cause changes of EMC and/or ripple values.
Protection class	I acc. EN 61140
Visual Indications	green LED U _{out} = Output voltage ok (DC ok.)
Case	19" cassette, 3U, 14TE, depth app. 166mm, elox alu front panel, RAL7035
Connection	Connector H15
Weight	app. 1,5 kg